

SC1 - 200 x 100 x 5 RHS HOT DIP GALVANISED
SB1 - 40 x 40 x 4 SHS DURAGAL

ELEVATION OF SIGNAGE
SCALE 1:50

SECTION 1
1:50 HORIZONTAL
1:50 VERTICAL


NOTES:

1. BORED FOUNDATIONS BEARING INTO 250 kPa DUCS NATURAL RESIDUAL: WEATHERED SANDY TO GRAVELLY CLAYS. IF WEATHERED SANDSTONE IS ENCOUNTERED BEFORE 2000mm DEPTH IS ACHIEVED, SOCKET 500 INOT WEATHERED ROCK (MINIMUM HOLE DPETH REQUIRED IS 1.5m IE (1000mm CLAY SAND + 500mm SOCKET TO WEATHERED ROCK).
2. CONCRETE PROPERTIES:
-FOUNDATIONS:N25.
3. SIGNAGE IS 6000mm WIDE x 3300 HIGH.



SITE PLAN
SCALE 1:500

SHORT LINES TABLE		
LINE	BEARING	DISTANCE
1	101°14'45"	6.045



Horizontal Scale 1:500 (A1)
1:1000 (A3)

REV	AMENDMENT	ISSUED	DATE
A	INITIAL ISSUE	DJE	XX/04/21
B	BOUNDARY DIMENSIONS ADDED	HOD	27/07/21



SYDNEY
P: 02 9659 0005
CENTRAL COAST
P: 02 4325 5255
HUNTER
P: 02 4966 8388
ABN: 26 134 067 842
www.brs.com.au
mail@brs.com.au

Client:

URBAN LAND & HOUSING PTY LTD

PROPOSED SIGNAGE PLAN FOR PART LOT4 DP 1256730

Designed: --
Drawn: DKH
Checked: DJE

Scales: Plan 1:500

Datum: N/A

Plan No.
ID 219809
File Ref.
14/46

Sheet No.
1
REV.
B